

Installation Instructions

Streamline Stainless Bars for 2007-10 Toyota Tundra

This installation uses Bracket Kit Part No. 14709 2007-10 Toyota Tundra Access Cab Pick Up uses 14080 Bars (80") 2007-10 Toyota Tundra Double Cab Pick Up 4 Dr uses 14090 Bars (90")

Parts List:

2-Front Mount Brackets 32-8mm Locking Washers 16–8mm Flat Washers 8 Clamping Top Plate brackets 6-Other Mount Brackets 16-1" Bracket Mounting Bolts with 13mm heads 8 1.25"Bar Mounting Carriage Bolts 8 13mm Nylock Nuts

Installation:

- 1 Remove contents from box and identify Front brackets for each side of the vehicle. Front brackets have an obtuse angle and one hole on each mounting surface. All other brackets have one mounting surface with holes adjacent to each other.
- 2 Locate factory pre-threaded holes under pinch weld of vehicle. These may have a plastic cap that will need to be removed with a standard screwdriver. Line up front bracket to factory holes and mount using 1" bolts with flat washers and lock washers. Repeat for all mounting bracket locations. Be sure to hand tighten only at this point to ensure proper alignment later.
- 3 Clamp Rampage Streamline step bars to brackets using Small Clamping Top Plate brackets, 1.25" Bar mounting carriage bolts, lock washers and nylock nuts. Helpful tip: Place top plate inside of bottom of Streamline bar and rotate to line up with main bracket attached to vehicle. The center pin on top plate bracket should line up with center hole on Main Bracket for safe and secure fastening of the Streamline step bar. Failure to properly align this pin in the center hole may keep the Step Bars from being securely fastened.
- 4 After insuring that all parts are properly aligned and step bar surface is level, tighten all bolts. Repeat steps 1 through 4 for opposite side of vehicle to complete installation of Rampage Streamline Tube Steps.