

Recommended Air Filter cleaning intervals:3000 Miles

US Patent# US 7,263,961B2

Application: 2005-06 LOTUS ELISE

Parts List: 1 x Weapon\*R Intake pipe. /1 x Weapon\*R Air Filter 3" /1 x 3" -3 "Coupler

1 x Intake System Bracket kit / 1 x 3" Clamp / 1 x 4mm Vacuum Cap

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Unbolt the Air Recirculator valve. leave plug connected, move aside.
- 3 Remove all 4mm vacuum hoses from OEM intake and engine, remove 4mm lines from engine bay.
- 4 Disconnect the MAF sensor harness, Remove the OEM air cleaner box by pulling upwards.
- 5 Remove the OEM rubber intake tube, carefully remove MAF sensor from OEM airbox.
- 6 Wipe the throttlebody clean of any grease, install the 3" -3" coupler onto throttlebody, secure with OEM clamp.
- 7 Insert Weapon\*R intake pipe into the 3" coupler, secure with clamp.
- 8 Install the 4mm vacuum cap onto the 4mm port on the intake manifold, left behind by the OEM 4mm hoses.
- 9 Install MAF sensor into Weapon\*R intake pipe, reconnect MAF sensor harness.
- 10 Install the Weapon\*R filter onto the end of the intake pipe.

## Note: Dragon / Secret Weapon Filter Option :

- 11 Stretch the 3"-3" coupler onto the intake pipe, secure with clamp.
- 12 Insert the Dragon or Secret Weapon air filter into the coupler, secure with supplied clamp.
- 13 Install U-shaped part of intake system bracket under the clamp on air filter.
- 14 Install the rubber mounting grommet to the closest hole to the Weapon\*R air filter.
- 15 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 16 Secure with washer and nut included in bracket kit.
- 17 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- **18** Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 19 Place Weapon\*R CARB Sticker on a visible place in engine compartment. ( If Applicable )

## WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Returned Products may be subject to a 25% restocking charge. INSTALLED PRODUCTS ARE NON-REFUNDABLE!







If you have any Question about this Product, Please refer to our website @ WWW.WEAPON-R.COM