



CARB PENDING

Recommended Air Filter Cleaning Intervals: 3000 Miles.

Part # 's **Secret Weapon: 308-123**

US Patent# US 7,263,961B2

Application : 2006 Range Rover Sport HSE 4.4L V8

**Parts List : 1 x Weapon*R 3.5" Intake pipe. / 1 x Weapon*R 4" Air Filter / 1 x 3.5"- 3.5" coupler
1 x 3.5"-4" coupler/ 1 x 15mm Hose / 1 x Intake Bracket kit / 4 x 4" clamps**

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Remove the 15mm PCV hose from OEM intake.
- 3 Unplug and remove the MAF sensor unit from the OEM air intake system, put aside.
- 4 Remove the OEM rubber intake tube, remove the OEM air cleaner box by pulling upwards.
- 5 Install the 3.5" -3.5" coupler onto throttlebody, secure with OEM clamp.
- 6 Insert Weapon*R intake pipe into the 3.5" side of coupler, secure with clamp.
- 7 Install the OEM 15mm hose onto the Weapon*R intake pipe and snap it on.
- 8 Install the 3.5"-4" coupler onto end of WR 3.5" tube and clamp down
- 9 Reinstall the MAF into the WR piping adapter and screw down with Allen screws
- 10 Clip OEM wire harness back into the OEM MAF sensor

Note: Secret Weapon Filter Option :

- 12 Install Secret Weapon air filter into the 4" side of the 3.5"-4" coupler on pipe and clamp down
- 13 Install filter assembly onto the MAF bracket plate, secure with OEM clamp.
- 14 Install U-shaped part of intake system bracket under the clamp on air filter.
- 15 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 16 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 17 Secure with washer and nut included in bracket kit.
- 18 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 19 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 20 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !**
Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.



Air Shield above was a custom made shield by Customer.

Pictures for the representation of the WR intake only

If you have any Question about this Product, Please refer to our website @ WWW.WEAPON-R.COM