

HP HEATSHIELD MAT™

HIGH-TEMPERATURE RADIANT HEAT MAT

Keep your cool in the heat with our HP Heatshield Mat™. When used in applications when there is 1" of airspace and air flow, the Heatshield Mat™ is capable of reflecting 90% of radiant heat. Face the aluminized side toward the source of radiant heat to shield heat away. This product withstands 1100°F of radiant heat (requires minimum of 1" of airspace) and up to 450°F of direct heat. The HP Heatshield Mat™ is available with a high temperature peel and stick adhesive.

INSULATION TYPE: RADIANT HEAT **USES:** HOODS, BODY PANELS, FLOOR BOARDS, FAIRINGS, FUEL CELLS, GAS TANKS, ENGINE ROOMS

PART NO.	DESCRIPTION
720305	HP HEATSHIELD MAT; 36" X 58"
720505	HP HEATSHIELD MAT; 60" X 58"
721005	HP HEATSHIELD MAT; 18" X 18" W/ ADHESIVE
721101	HP HEATSHIELD MAT; 12" X 12" W/ ADHESIVE
721102	HP HEATSHIELD MAT; 1' X 2' W/ ADHESIVE
721202	HP HEATSHIELD MAT; 2' X 2' W/ ADHESIVE
721305	HP HEATSHIELD MAT; 36" X 58" W/ ADHESIVE
721505	HP HEATSHIELD MAT; 60" X 58" W/ ADHESIVE

APPLICATIONS:



RATED TO:

1100°



*ALUMINIZED
FIBERGLASS WITH
ADHESIVE BACKING*

*APPLIES WITH
HIGH-TEMP GLUE,
SILICONE, RIVETS OR
SCREWS*

*STOPS HEAT FROM
ENTERING THE VEHICLE*

LAVA MAT™

RUGGED RADIANT HEAT SHIELD

Don't be tricked by the "fool's gold"! Lava Mat™ outperforms that gold foil vinyl sticker stuff by reflecting 60% more radiant heat. Made from crushed volcanic rock, our Lava Mat™ has similar benefits as our HP Heatshield Mat™ with that trick carbon fiber look! This heat shield insulator helps to reflect radiant heat away to provide an air box heat shield or a heat shield barrier for your carbon fiber or fiberglass hood. Our Lava Mat™ can also be laid on a fire wall to shield radiant heat and give your vehicle that trick carbon fiber look. Our Lava Mat™ withstands 1200°F direct continuous and 1800°F intermittent.

INSULATION TYPE: RADIANT HEAT AND DIRECT CONTACT **USES:** HOODS, BODY PANELS, FLOOR BOARDS, FAIRINGS, FUEL CELLS, GAS TANKS, ENGINE ROOMS

PART NO.	DESCRIPTION
770001	LAVA MAT™; 12" X 24"; W/ ADHESIVE
770002	LAVA MAT™; 24" X 24"; W/ ADHESIVE
770003	LAVA MAT™; 36" X 48"; W/ ADHESIVE
770005	LAVA MAT™; 60" X 48"; W/ ADHESIVE
781003	LAVA MAT™; 36" X 47" ; HEAVY DUTY W/ ADHESIVE
781005	LAVA MAT™; 60" X 47" ; HEAVY DUTY W/ ADHESIVE

APPLICATIONS:



RATED TO:

1800°



*WITHSTANDS 1200°F
DIRECT CONTINUOUS AND
1800°F INTERMITTENT*

*ADHESIVE BACKING FOR
EASY APPLICATION*

*MADE FROM CRUSHED
VOLCANIC ROCK*