










Installation Instructions:
JLT 2007-09 GT500 Fresh Air Kit
#JLTFAK-GT500

Thank you for purchasing our product. We hope you are satisfied with the look and performance. Take your time and it will be a smooth install.

Please review complete instructions prior to installing.

Step#	
1	Verify you have all of the following parts included in the kit: (1) Bracket, (1) 20" Section of Air Duct Hose, (1) 74" Section of Air Duct Hose, (2) 40 Hose Clamps, (6) Zip ties <i>Optional: (2) Grille Bezels with Foam plugs</i>
2	Gather all of the following tools needed for the installation: 5/16 Nut Driver, 2 ¼" hole saw, 10mm wrench or ratchet and socket, angle drill or drill with extensions
3	Raise car to good working height using lift or jack and jack stands.
4	Using your drill and the 2 ¼" hole saw drill from the back side of the bumper through the grille. Using a small angle drill or flexible extension will help. You can remove the bumper if you do not have the angle drill. You can also use a small air ratchet and socket if your hole saw has a hex shaft. See picture: <div style="display: flex; justify-content: space-around;">   </div>
5	Using silver 10mm bolt on lower flange of drivers side headlight attach Fresh Air mounting bracket: <div style="text-align: center;">  </div>

6	<p>Starting with the drivers side, install 1 clamp on the end of the 20" air duct hose and clamp on to bumper port and route up into the guide bracket installed in previous step.</p>  
7	<p>Attach clamp to 74" air duct hose and clamp to passenger side bumper port as you did the drivers side.</p>
8	<p>Route hose along the back side of the radiator support and attach hose to the sway bar using supplied zip ties. Install hose in guide bracket with driver's side hose.</p>  
9	<p>If you have the JLT aluminum Grille Bezels, simply snap them in and you are done.</p>

Thanks for the business. If you have any questions, please e-mail Jay@JLTtruecoldair.com or call 757-335-1940. Our hours are 8:00am – 5:00pm Eastern Time.

Warranty: JLT Performance Inc. will repair or replace any part of their product found upon our inspection to be defective in workmanship or material within 1 year from the purchase date for the original purchaser.

Disclaimer: JLT Performance Inc. makes no warranties whatsoever, expressed or implied, oral or written to any purchasers, except the warranty above. JLT Performance Inc. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by JLT Performance Inc. agree to hold harmless and indemnify JLT Performance Inc. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to JLT Performance Inc. for any claims arising out of use of its products.

Custom Paint Disclaimer: All custom paint jobs are done by JLT Performance Inc. Every job is different and done by hand. By ordering a custom paint job, you accept this fact and cannot hold JLT Performance Inc. liable for the end result not being exactly what you had in your mind.

Return Policy: All returns will be subject to a 10%-25% restocking fee. Air Filters will not be accepted for return unless they are in original plastic sealed bag. Please visit www.JLTtruecoldair.com for complete return policy.