

Installation Sheet

□Application Vehicle

2003∼	Year	Mitsubishi Lancer Evolution	Vehicle Name
4G63	Engine Type	olution	
103BKM04	Product Code	СТ9А	Vehicle Code

□Parts List

[[
No	Part Name	Size	Qty	Qty No.	Part Name	Size	Qty
Θ	Front Muffler	Vehicle Specific	1	② Nut	Nut	M10×P1.25	2
2	Main Muffler	Vehicle Specific	1	8	8 Washer	M12	2
ω	③ Gasket	P102× <i>φ</i> 71	1	9	Washer	M10	4
4	Gasket	P106× φ75	1	10	Bolt	M18×P1.5×L11	_
(5)	Bolt	$M10 \times P1.25 \times L40$	2	(1)	Instruction Manual		_
<u></u>	Nut	M12×P1.25	2				

□Exhaust System Installation Procedure

1.Install the muffler according to the diagram below and hand tighten the nuts and bolts in place

XThe diagram only shows partial usage of the nuts and bolts. Please use all of them.

2. Take note of piping clearance, gasket positioning, tip position, chassis clearance and tighten

the nuts and bolts into position. Start from the catalytic converter side and work your way back

Torque Specification M10 43∼5

43~55N m 4.4~5.6 kgf m 31.8~40.5lb ft 46~59N m 4.7~6.0 kgf m 33.9~43.5lb ft

3.Be sure to confirm tail pipe positioning so that it does not touch the rear bumper. If the positioning unnecessary sound and may melt the bumper.
CAUTION is off, loosen the nuts and bolts and adjust accordingly. Failure to provide adequate clearance may cause

Be sure to check clearances between brake components, fuel line, and drive train components.

□Checkpoints after Installation

1. After installation, move the exhaust system side to side by hand to confirm clearances.

2. Rev the engine to 2500 rpm to check for any exhaust leaks

3. Test drive the vehicle and check for exhaust leaks or unusual sounds.

4.If anything usual occurs in steps $1\sim3$, reinstall the muffler system.

5.Retighten all of the nuts and bolts after $100 \sim 200$ mi.

