

Exhaust System

Installation Sheet

□Application Vehicle

1996~2000	Year	Honda Civic Hatchback DX	Vehicle Name
D16Y7	Engine Type	ack DX	
104BKH09	Product Code	EJ6	Vehicle Code

□Parts List

		Instruction Manual	<u>®</u>	2	ϕ 61.5 × P90	Gasket	4
8	M10	② Washer	(7)	1	Vehicle Specific	Main Muffler	ω
4	M10×P1.25	Nut	6	1	Vehicle Specific	Middle Muffler	2
4	M10×P1.25×L40	⑤ Bolt	(5)	1	Vehicle Specific	① Front Muffler	\ominus
Qty	Size	Part Name	Qty No.	Qty	Size	Part Name	No.

□Exhaust System Installation Procedure

XThe diagram only shows partial usage of the nuts and bolts. Please use all of them. 1.Install the muffler according to the diagram below and hand tighten the nuts and bolts in place.

2. Take note of piping clearance, gasket positioning, tip position, chassis clearance and tighten

the nuts and bolts into position. Start from the catalytic converter side and work your way back

Torque Specification M10 43∼

43~55N m 4.4~5.6 kgf m 31.8~40.5lb ft

3.Be sure to confirm tail pipe positioning so that it does not touch the rear bumper. If the positioning is off, loosen the nuts and bolts and adjust accordingly. Failure to provide adequate clearance may cause unnecessary sound and may melt the bumper.

[CAUTION]

Be sure to check clearances between brake components, fuel line, and drive train components.

☐ Checkpoints after Installation

After installation, move the exhaust system side to the side by hand to confirm clearances

2.Rev the engine to 2500rpm to check for any exhaust leaks.

3. Test drive the vehicle and check for exhaust leaks or unusual sounds.

4.If anything usual occurs in steps $1\sim3$, reinstall the muffler system.

5.Retighten all of the nuts and bolts after 200 \sim 300km.

