

Installation Sheet

□Application Vehicle

D16Z6/B16A2	1992~2000
Engine Type	Year
Civic Coupe EX/Si	Honda Civic Co
ne	Vehicle Name

⊔Parts List

			€	S	φ 61.5 × P90	(F) Gasket	<u></u>
		Apex Instruction Manual	9	_	φ 61.5 × PCD86	4 Gasket	4
1	M10	8 Washer	@	_	Vehicle Specific	Apex Main Muffler Vehicle Specific	ω
	M10 × P1 25	⑦ Nut	9	_	Vehicle Specific	Apex Middle Muffler Vehicle Specific	0
t —	M10 × P1 25 × L40	Bolt	<u></u>	_	Vehicle Specific	Apex Front Muffler Vehicle Specific	\ominus
Qty	Size	Part Name	Qty No.	Qty	Size	Part Name	No.

□Apex Exhaust System Installation Procedure

1.Install the muffler according to the diagram below and hand tighten the nuts and bolts in place.

XThe diagram only shows partial usage of the nuts and bolts. Please use all of them.

2. Take note of piping clearance, gasket positioning, tip position, chassis clearance and tighten the nuts and bolts into position. Start from the catalytic converter side and work your way back

Torque Specification M 6 5~ $5\sim$ 7N·m 0.5 \sim 0.6 Kgf·m 3.6 \sim 4.4lb·ft 43 \sim 55N·m 4.4 \sim 5.6 Kgf·m 31.8 \sim 40.5lb·ft

3.Be sure to confirm tail pipe positioning so that it does not touch the rear bumper. If the positioning unnecessary sound and may melt the bumper. is off,loosen the nuts and bolts and adjust accordingly. Failure to provide adequate clearance may cause

Be sure to check clearances between brake components, fuel line, and drive train components.

☐Checkpoints after Installation

After installation, move the exhaust system side to the side by hand to confirm clearances

2. Rev the engine to 2500 rpm to check for any exhaust leaks.

4.If anything usual occurs in steps $1\sim3$, reinstall the muffler system. 5.Retighten all of the nuts and bolts after 200 \sim 300km.

3. Test drive the vehicle and check for exhaust leaks or unusual sounds.

