## MPEXi<sub>®</sub> Exhaust System

### Installation Sheet

### □Application Vehicle

Year	Honda (
ar	Civic Hatchback
Engine Type	
Vpe	VDe
Anex Product Code	EJ6  Apex Product Code
	Honda Civic Hatchback DX

#### □Parts List

nua	8 Apex Instruction Manual	<u>@</u>	2	$P90 \times \phi 61.5$	4 Gasket	4
	⑦ Washer	9	_	Vehicle Specific	Apex Main Muffler	ω
	® Nut	69	_	Vehicle Specific	Apex Middle Muffler Vehicle Specific	0
ı	⑤ Bolt	(J)	_	Vehicle Specific	Apex Front Muffler	$\ominus$
l .	Part Name	Qty No.	Qty	Size	Part Name	No.

# □Apex Exhaust System Installation Procedure

1.Install the muffler according to the diagram below and hand tighten the nuts and bolts in place.

The diagram only shows partial usage of the nuts and bolts. Please use all of them.

Take note of piping clearance, gasket positioning, tip position, chassis clearance and tighten

the nuts and bolts into position. Start from the catalytic converter side and work your way back

Torque Specification M 6 5~

M10  $5\sim 7 \text{N·m} \ 0.5\sim 0.6 \text{ kgf·m} \ 3.6\sim 4.4 \text{lb·ft}$  $43\sim 55 \text{N·m} \ 4.4\sim 5.6 \text{ kgf·m} \ 31.8\sim 40.5 \text{lb·ft}$ 

3.Be sure to confirm tail pipe positioning so that it does not touch the rear bumper. If the positioning unnecessary sound and may melt the bumper. is off, loosen the nuts and bolts and adjust accordingly. Failure to provide adequate clearance may cause

Be sure to check clearances between brake components, fuel line, and drive train components.

## ☐ Checkpoints after Installation

After installation, move the exhaust system side to side by hand to confirm clearances

2.Rev the engine to 2500rpm to check for any exhaust leaks.

3. Test drive the vehicle and check for exhaust leaks or unusual sounds.

4.If anything usual occurs in steps  $1\sim3$ , reinstall the muffler system.

5.Retighten all of the nuts and bolts after 100 $\sim$ 200mi

